



GALVANIZED HEXAGONAL WIRE NETTING

Materials: superior low carbon steel wire, stainless steel wire.

Weaving pattern: Normal twist, reverse twist

Process: electric galvanizing or hot dipped zinc plating after weaving; galvanized before weaving

Characteristics:

Galvanized hexagonal wire nettings enjoy many excellent characteristics, such as good corrosion resistance, acid resistance, alkali resistance, weather resistance, anti-oxidizing property and a long service life.

Besides galvanized hexagonal wire netting is firm in structure and flat in surface therefore it has a beautiful appearance..

Assortments Available:

Hexagonal Wire Netting Electro Galvanized before Weaving

Hexagonal Wire Netting Electro Galvanized After Weaving

Hexagonal Wire Netting Hot Dipped Galvanized before Weaving

Hexagonal Wire Netting Hot Dipped Galvanized after Weaving

Hexagonal Wire Netting PVC Coated Before or After Weaving

Other Hexagonal Wire Netting



Applications:

As reinforcement, protection and heat preservation material in construction, petroleum, chemical industry, breeding, foodstuff industry, garden fencing and

fences for animals like chicken, ducks, rabbits and prevention netting of residence.

Specifications of galvanized hexagonal wire netting:

Galvanized Hexagonal Wire Netting					
Mesh			Min. Gal.v.	Width	Wire Gauge (Diameter)
Inch	mm	Tolerance(mm)	G/SQ.M		BWG
3/8"	10mm	±1.0	0.7mm - 145	2' - 1M	27, 26, 25, 24, 23
1/2"	13mm	±1.5	0.7mm - 95	2' - 2M	25, 24, 23, 22, 21
5/8"	16mm	±2.0	0.7mm - 70	2' - 2M	27, 26, 25, 24, 23, 22
3/4"	20mm	±3.0	0.7mm - 55	2' - 2M	25, 24, 23, 22, 21, 20, 19
1"	25mm	±3.0	0.9mm - 55	1' - 2M	25, 24, 23, 22, 21, 20, 19, 18
1-1/4"	31mm	±4.0	0.9mm - 40	1' - 2M	23, 22, 21, 20, 19, 18
1-1/2"	40mm	±5.0	1.0mm - 45	1' - 2M	23, 22, 21, 20, 19, 18
2"	50mm	±6.0	1.2mm - 40	1' - 2M	23, 22, 21, 20, 19, 18
2-1/2"	65mm	±7.0	1.0mm - 30	1' - 2M	21, 20, 19, 18
3"	75mm	±8.0	1.4mm - 30	2' - 2M	20, 19, 18, 17
4"	100mm	±8.0	1.6mm - 30	2' - 2M	19, 18, 17, 16

Note:

1.) The above tolerance comply with standard EN10223-2:1997;

2.) Minimum Galvanization is only for typical wire diameter as stipulated separately in the column for your reference; Also it is only for hot dipped Galvanized Netting.

PVC Coated Hexagonal Wire Netting			
Mesh		Wire Gauge (MM)	Width
Inch	MM	-	-
1/2"	13mm	0.6mm - 1.0mm	2' - 2M
3/4"	19mm	0.6mm - 1.0mm	2' - 2M
1"	25mm	0.7mm - 1.3mm	1' - 2M
1-1/4"	30mm	0.85mm - 1.3mm	1' - 2M
1-1/2"	40mm	0.85mm - 1.4mm	1' - 2M
2"	50mm	1.0mm - 1.4mm	1' - 2M
We also offer other specifications you need			

Note:

The thickness of PVC Coating is usually 0.2-0.4mm, others may arranged as per buyers' request;

Package: Normally each roll packed in water proof paper, then in termo foil (Shrunked Plastic);